



SLOAN®

# The New Dual Flush Touch-Free Sensor Flushing System

Easy to use - Reliable - Contactless  
Germ-free, Electronic Flushing System



# The New Dual Flush Touch-Free Sensor Flushing System



Flushing system installed in cavity or in-ceiling


## Product Code:

42070M

- Mains Pressure 6/3 Litre

42071L


- Tank Fed Pressure 6/3 Litre



## Product Code:

DFTF4281

Square Panel  
300mm x 300mm



## Product Code:

DFTF4282

Rectangle Panel  
175mm x 100mm



## Description

In-wall, touch-free dual flush flushing system

## Applications

This product is perfect for:  
Commercial Office Buildings, Schools, Hospitals, Shopping Centres, Public Restrooms and other Applications.

## Benefits

- Contactless and Germ-Free
- A healthier and safer environment
- Increased efficiency
- Reduces water waste
- Prolonged lifespan

## Features

- Touch-free Infrared sensing technology
- Robust stainless steel panel with an internal mounting frame
- Visual feedback for guaranteed operation
- Repeat flushing in 3 seconds
- Will only repeat flush cycle if hand is removed
- Simple 24 VAC power pack operation
- Sensing distance adjustability
- Mains and Tank Pressure Applications
- Retrofit Changeover to other brands (subject to verifications)
- Years of reliable touch-free performance
- 2 plate options:

175mm x 100mm if valve is in ceiling space

300mm x 300mm if valve is within the wall/cavity

## How to Operate

- Place hand within 75 mm of sensor for less than 1.5 seconds for half flush operation
- Place hand within 75 mm of sensor for greater than 2 seconds for full flush operation

## Space Requirements

- Minimum wall cavity = 140mm deep
- Minimum width of assembly = 270mm wide
- Minimum height of assembly = 200mm height



[www.magriffith.com.au](http://www.magriffith.com.au)

T (03) 9399 8444 F (03) 9399 8446 E [sales@magssp.com.au](mailto:sales@magssp.com.au)