

MAG Foot Operated Valves

Self Closing



Heavy Duty option Model **49011**



Light Duty option Model **49012**

Product Information

- Self closing with foot activation
- Chrome plated, brass body
- Min pressure 70kPa
- Max. pressure 350kPa
- ½" BSP Female inlet and outlet
- Installation Kit incl. Outlet, Flexible Connector, 2 x Mini Stops

Features and Benefits

- Automatic shut off, saves water
- Mechanical Operation
- Hygienic, Robust and Durable
- Straight body or 45° angled body options
- Energy efficient, practical solutions
- 12 month warranty*

Product Code

Code	Description
49011	Lugged Foot Valve, Straight Body
49013	Lugged Foot Valve Installation Kit, Straight Body
49012	Lugged Foot Valve, 45° Angled Body
49014	Lugged Foot Valve, Installation Kit, 45° Angled Body

MAG Foot Operated Valves

Specification Sheet



Parts	Measurements
Reach	115mm
Min. hole required	32mm
Max. hole required	38mm
Base of flange to top of spout	150mm
All Thread	85mm

Parts	Measurements
Base to the top of the button	75mm
Depth	120mm
Width	80mm



Model **49013** - Lugged Foot Valve, Installation Kit, Straight Body

Dimensional Data (mm) are Subject to Manufacturing Tolerances and Change Without Notice

MAG Foot Operated Valves

Specification Sheet



Parts	Measurements
Base to the top of the button	80mm
Depth	75mm
Width from inlet to outlet	60mm



Model **49014** - Lugged Foot Valve, Installation Kit, 45° Angled Body

Dimensional Data (mm) are Subject to
Manufacturing Tolerances and Change Without Notice